

Samsung 403T LCD Display

The First LCD with Integrated Multi-Input Display



Perfect for 24/7 control room applications, retail display, video conferencing or anywhere else a large, bright, easy-to-read display is required.

Features

- o Display Video and Data Inputs Side-by-Side
- o Innovative On-Screen Control Panel for Fast and Easy Display Management
- o Ultra Slim 3.9" Depth
- o 60,000 Hour Lamp
- o 16:9 Contrast Ratio
- o Low Power Consumption
- o 170 Degree Viewing Angle

Product Specifications

Panel	TFT/PVA
Viewable Size	40"
Native Resolution (Optimum)	1280 x 768
Maximum Resolution	1280 x 768
Pixel Pitch (mm)	0.681
Brightness (Typical)	500 cd/m ²
Contrast Ratio	600:1
Colors Supported	16.7M
Viewing Angle (H/V)	170°/170°
Interface	Analog/Digital Analog RGB, DVI Digital Link, S-Video, Component/HDTV
Input Video Signal	Separate H/V, Composite H/V, SOG
Sync Type	15-Pin D-Sub, DVI-D, S-Video, BNC Connector, Component, HDTV, External Control, Audio
Input Connectors	
Horizontal Frequency (kHz) – Analog	31 – 70
Horizontal Frequency (kHz) – Digital	31 – 50
Vertical Frequency (Hz)	55 – 85 (60Hz @ WXGA)
Bandwidth (MHz)	100
Plug and Play	DDC 1/2B
Wall Mount	Optional
Power Consumption (Max)	220 Watts (Max)
Emission Standard	TCO '95
Multimedia Speakers	Optional
Mac Compatibility	Yes
Sun Compatibility	Yes
Dimensions (W x H x D)	38.3" x 26.5" x 3.9"
Net Weight	58.2 Lbs.
Parts/Labor/Backlight Warranty (Years)	3/3/3
Available Colors	Black

Total Solutions. One Resource.